

## HEYClip™ Lockit™ Loops and Clips Standoff Loops - Blind Mount

| MAXIMUM BUNDLE DIAMETER                                       |      | PART NO.<br>Natural | DESCRIPTION | SPACER HEIGHT<br>A |      | OVERALL LENGTH ABOVE PANEL<br>C |      | MOUNTING HOLE DIAMETER |     |
|---|------|---------------------|-------------|--------------------|------|---------------------------------|------|------------------------|-----|
| in.   | mm.  |                     |             | in.                | mm.  | in.                             | mm.  | in.                    | mm. |
| <b>BMLL Series</b> For .25" (6,4 mm) Minimum Thickness Panels |      |                     |             |                    |      |                                 |      |                        |     |
| .28   | 7,0  | 4052M               | BMLL 28-16  | .16                | 4,0  | .91                             | 23,1 | .312                   | 7,9 |
|   |      | 4052                | BMLL 28-19  | .19                | 4,8  | .94                             | 23,9 |                        |     |
|   |      | 4053                | BMLL 28-50  | .50                | 12,7 | 1.25                            | 31,8 |                        |     |
|   |      | 4260                | BMLL 28-75  | .75                | 19,1 | 1.50                            | 38,2 |                        |     |
| .39   | 10,0 | 4056                | BMLL 39-19  | .19                | 4,8  | 1.10                            | 27,9 |                        |     |
|   |      | 4057                | BMLL 39-50  | .50                | 12,7 | 1.41                            | 35,8 |                        |     |
|   |      | 4261                | BMLL 39-75  | .75                | 19,1 | 1.66                            | 42,2 |                        |     |
| .50   | 12,5 | 4175                | BMLL 50-19  | .19                | 4,8  | 1.28                            | 32,5 |                        |     |
|   |      | 4176                | BMLL 50-50  | .50                | 12,7 | 1.59                            | 40,4 |                        |     |
|   |      | 4177                | BMLL 50-75  | .75                | 19,1 | 1.84                            | 46,8 |                        |     |
| .59   | 15,0 | 4180M               | BMLL 59-16  | .16                | 4,0  | 1.44                            | 36,5 |                        |     |
|   |      | 4180                | BMLL 59-19  | .19                | 4,8  | 1.47                            | 37,3 |                        |     |
|   |      | 4181                | BMLL 59-50  | .50                | 12,7 | 1.78                            | 45,2 |                        |     |
|   |      | 4182                | BMLL 59-75  | .75                | 19,1 | 2.03                            | 51,6 |                        |     |

Standard color natural.

## Standoff Lockit™ Clips - Arrowhead Mount


| MAXIMUM BUNDLE DIAMETER                                 |      | PART NO.<br>Natural | DESCRIPTION  | SPACER HEIGHT<br>A |      | OVERALL LENGTH ABOVE PANEL<br>C |      | MOUNTING HOLE DIAMETER |     | STYLE |
|---|------|---------------------|--------------|--------------------|------|---------------------------------|------|------------------------|-----|-------|
| in.   | mm.  |                     |              | in.                | mm.  | in.                             | mm.  | in.                    | mm. |       |
| <b>PMLC Series</b> For Panels up to .06" (1,6 mm) thick |      |                     |              |                    |      |                                 |      |                        |     |       |
| .25   | 6,4  | 4185                | PMLC 25-19   | .19                | 4,8  | .72                             | 18,3 | .187                   | 4,8 | 1     |
|   |      | 4186                | PMLC 25-25   | .25                | 6,4  | .78                             | 19,9 |                        |     |       |
|   |      | 4187                | PMLC 25-37   | .37                | 9,5  | .91                             | 23,0 |                        |     |       |
|   |      | 4188                | PMLC 25-50   | .50                | 12,7 | 1.03                            | 26,2 |                        |     |       |
|   |      | 4189                | PMLC 25-63   | .63                | 15,9 | 1.16                            | 29,4 |                        |     |       |
|   |      | 4190                | PMLC 25-100  | 1.00               | 25,4 | 1.53                            | 39,9 |                        |     |       |
| For Panels from .03" (0,8 mm) - .08" (2,0 mm) thick     |      |                     |              |                    |      |                                 |      |                        |     |       |
| .44   | 11,1 | 14185F              | PMLC 43-19   | .19                | 4,8  | .98                             | 24,9 | .187                   | 4,8 | 1     |
|   |      | 14186F              | PMLC 43-25   | .25                | 6,4  | 1.04                            | 26,5 |                        |     |       |
|   |      | 14187F              | PMLC 43-37   | .37                | 9,5  | 1.17                            | 29,6 |                        |     |       |
|   |      | 14188F              | PMLC 43-50   | .50                | 12,7 | 1.29                            | 32,8 |                        |     |       |
|   |      | 14189F              | PMLC 43-63   | .63                | 15,9 | 1.42                            | 36,0 |                        |     |       |
|   |      | 14190F              | PMLC 43-100  | 1.00               | 25,4 | 1.79                            | 45,5 |                        |     |       |
| .47   | 11,9 | 4345                | PMLC 50-19   | .19                | 4,8  | .96                             | 24,4 | .187                   | 4,8 | 2     |
|   |      | 4346                | PMLC 50-25   | .25                | 6,4  | 1.02                            | 26,0 |                        |     |       |
|   |      | 4347                | PMLC 50-37   | .37                | 9,5  | 1.15                            | 29,1 |                        |     |       |
|   |      | 4348                | PMLC 50-50   | .50                | 12,7 | 1.27                            | 32,3 |                        |     |       |
| .73   | 18,5 | 4191                | PMLC 73-19   | .19                | 4,8  | 1.22                            | 30,9 | .187                   | 4,8 | 2     |
|   |      | 4192                | PMLC 73-25   | .25                | 6,4  | 1.28                            | 32,5 |                        |     |       |
|   |      | 4193                | PMLC 73-37   | .37                | 9,5  | 1.40                            | 35,6 |                        |     |       |
|   |      | 4194                | PMLC 73-50   | .50                | 12,7 | 1.53                            | 38,8 |                        |     |       |
| For Panels from .08" (2,0 mm) - .16" (4,0 mm) thick     |      |                     |              |                    |      |                                 |      |                        |     |       |
| .47   | 11,9 | 4366                | PMLC 50-19-1 | .19                | 4,8  | .96                             | 24,4 | .187                   | 4,8 | 2     |
|   |      | 4367                | PMLC 50-25-1 | .25                | 6,4  | 1.02                            | 26,0 |                        |     |       |
|   |      | 4368                | PMLC 50-37-1 | .37                | 9,5  | 1.15                            | 29,1 |                        |     |       |
|   |      | 4369                | PMLC 50-50-1 | .50                | 12,7 | 1.27                            | 32,3 |                        |     |       |
| .73   | 18,5 | 4195                | PMLC 73-19-1 | .19                | 4,8  | 1.22                            | 30,9 | .187                   | 4,8 | 2     |
|   |      | 4196                | PMLC 73-25-1 | .25                | 6,4  | 1.28                            | 32,5 |                        |     |       |
|   |      | 4197                | PMLC 73-37-1 | .37                | 9,5  | 1.40                            | 35,6 |                        |     |       |
|   |      | 4198                | PMLC 73-50-1 | .50                | 12,7 | 1.53                            | 38,8 |                        |     |       |

Standard color natural.



- Part Description Key: BMLL XX-YY, where XX = Maximum Bundle Diameter (inches) and YY = Height Above Panel (inches).
- For Quick Specs see page 7-50.


**NEW!**




**NEW!**



- Locking ends click into place.
- Part Description Key: PMLC XX-YY, where XX = Maximum Bundle Diameter (inches) and YY = Height Above Panel (inches).
- PMLC 43-series molded from natural V-0 material.
- For Quick Specs see page 7-50.



Style 1



Style 2