





# Heyco® Metal Locknuts

## NPT Thread Locknuts

Straight NPS Threads for use with NPT Threaded Fittings



Stamped Steel Nut




Zinc Die-cast Nut

TYPE TRADE SIZE	STAMPED STEEL		ZINC DIE-CAST	
	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
1/2	2250	LN 1/2	9800	LN 1/2 DC
3/4	2251	LN 3/4	9801	LN 3/4 DC
1	2252	LN 1	9802	LN 1 DC
1-1/4	9806	LN 1-1/4	9803	LN 1-1/4 DC
1-1/2	9807	LN 1-1/2	9804	LN 1-1/2 DC
2	9808	LN 2	9805	LN 2 DC

## PG Thread Locknuts–Nickel Plated Brass



THREAD SIZE	PART NO.	DESCRIPTION	PART DIMENSIONS			
			A Thickness		B Wrenching Flats	
			in.	mm.	in.	mm.
PG 7	2257	LN PG 7	.110	2,8	.591	15,0
PG 9	2258	LN PG 9	.110	2,8	.709	18,0
PG 11	2259	LN PG 11	.118	3,0	.827	21,0
PG 13.5	2260	LN PG 13	.118	3,0	.906	23,0
PG 16	2261	LN PG 16	.118	3,0	1.024	26,0
PG 21	2262	LN PG 21	.138	3,5	1.261	32,0
PG 29	2263	LN PG 29	.158	4,0	1.615	41,0
PG 36	2268	LN PG 36	.197	5,0	2.009	51,0
PG 42	2269	LN PG 42	.197	5,0	2.364	60,0



## Metric Thread Locknuts–Nickel Plated Brass

THREAD SIZE	PART NO.	DESCRIPTION	PART DIMENSIONS			
			A Thickness		B Wrenching Flats	
			in.	mm.	in.	mm.
M6	2243	LN M6	.110	2,8	.354	9,0
M8	2244	LN M8	.110	2,8	.433	11,0
M10	2245	LN M10	.110	2,8	.512	13,0
M12	2246	LN M12	.118	3,0	.591	15,0
M16	2247	LN M16	.118	3,0	.748	19,0
M20	2248	LN M20	.138	3,5	.945	24,0
M25	2249	LN M25	.138	3,5	1.181	30,0
M32	2253	LN M32	.177	4,5	1.417	36,0
M40	2254	LN M40	.177	4,5	1.811	46,0
M50	2255	LN M50	.217	5,5	2.165	55,0

- For use with Heyco-Flex™ Cordgrips and most electrical fittings.
- Nickel-plated brass finish over brass provides excellent corrosion resistance and durability.
- Metric sizes M6 thru M50 accommodate a wide range of fittings.