



Heyco® Liquid Tight Cordgrips Multi-Hole, NPT Hubs

- All accompanying Cordgrips are made of nylon construction with TPE sealing glands that resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents. This feature is not assessed by UL.
- **Locknuts not included.** For nylon locknut specifications or to order locknuts separately, see page 2-21.
- For body part dimensions see page 2-11.
- Multi-hole glands are only to be used with Heyco Liquid Tight Cordgrips and are not sold separately.
- Consult Heyco for cordgrips molded in other colors.

PART NO. Black	DESCRIPTIONS	GLAND CONFIGURATIONS
M3228GH	LTCG 3/8	2- 1,7 mm holes
M3228GP	LTCG 3/8	2- 3,0 mm holes
M3228GJ	LTCG 3/8	3- 1,7 mm holes
M3228GAP	LTCG 3/8	4- 1,4 mm holes
M3228GK	LTCG 3/8	4- 1,7 mm holes
M3228GM	LTCG 3/8	4- 2,3 mm holes
M3228GG	LTCG 3/8	5- 1,6 mm holes
M3228GAZ	LTCG 3/8	6- 1,4 mm holes
M3228GE	LTCG 3/8	10-1,4 mm holes
M3231GN	LTCG 1/2	2- 2,5 mm holes
M3231GT	LTCG 1/2	2- 3,8 mm holes
M3231GAB	LTCG 1/2	2- 4,2 mm holes
M3231GAC	LTCG 1/2	2- 5,0 mm holes
M3231GAE	LTCG 1/2	2- 5,2 mm holes
M3231GL	LTCG 1/2	3- 2,0 mm holes
M3231GQ	LTCG 1/2	3- 3,0 mm holes
M3231GX	LTCG 1/2	3- 4,0 mm holes
M3231GS	LTCG 1/2	6- 3,0 mm holes
M3231GZA	LTCG 1/2	9,9 x 4,9 mm flat
M3231GZB	LTCG 1/2	10,7 x 5,3 mm flat
M3200GAJ	LTCG LL1/2	2- 6,0 mm holes
M3200GQ	LTCG LL1/2	3- 3,0 mm holes
M3200GX	LTCG LL1/2	3- 4,0 mm holes
M3200GAH	LTCG LL1/2	3- 5,6 mm holes
M3200GR	LTCG LL1/2	4- 3,0 mm holes
M3200GY	LTCG LL1/2	4- 4,0 mm holes
M3200GZ	LTCG LL1/2	5- 4,0 mm holes
M3200GS	LTCG LL1/2	6- 3,0 mm holes
M3200GW	LTCG LL1/2	6- 3,8 mm holes
M3200GBB	LTCG LL1/2	6- 4,0 mm holes

PART NO. Black	DESCRIPTIONS	GLAND CONFIGURATIONS
M3234GAN	LTCG 3/4	2- 7,4 mm holes
M3234GAQ	LTCG 3/4	2- 8,0 mm holes
M3234GAF	LTCG 3/4	3- 5,2 mm holes
M3234GAM	LTCG 3/4	3- 7,0 mm holes
M3234GAD	LTCG 3/4	4- 5,0 mm holes
M3234GAG	LTCG 3/4	4- 5,2 mm holes
M3234GBC	LTCG 3/4	4- 6,0 mm holes
M3234GZA	LTCG 3/4	9,9 x 4,9 mm flat
M3234GZB	LTCG 3/4	10,7 x 5,3 mm flat
M3234GZE	LTCG 3/4	8,9 x 4,5 mm flat
M3234GZF	LTCG 3/4	10,7 x 4,8 mm flat
M3234GZG	LTCG 3/4	16,1 x 4,8 mm flat
M8437GAS	LTCG 1	4- 9,0 mm holes
M8437GAX	LTCG 1	4- 9,5 mm holes
M8437GAL	LTCG 1	6- 6,5 mm holes
M8437GZH	LTCG 1	17,5 x 4,8 mm flat
M4524GAT	LTCG 1-1/4	5- 9,0 mm holes
M4524GAL	LTCG 1-1/4	6- 6,5 mm holes
M4524GAR	LTCG 1-1/4	6- 8,0 mm holes
M4524GAW	LTCG 1-1/4	7- 9,0 mm holes

Standard color black.

Quick Specs

Material	6/6 Nylon with TPE sealing gland
Flammability Rating	94V-2 Standard
Temperature Rating	-22°F (-30°C) to 212°F (100°C)
IP Rating	IP 68