



Heyco® RDD Lockit™ Strain Relief Bushings





For Round Cables



WILL FIT THESE CABLES				PANEL DIMENSIONS				PART NO.	DESCRIPTION
UL Type Designation	AWG Conductors	Approximate Size		Mounting Hole Size		Thickness			
		in.	mm.	in.	mm.	in.	mm.		
SJ	18/2	.340	8,6	.875 w/	22,2 w/	.032	0,8	1861	RDD 301
SJO	14/2	.430	10,9	.770 flats	19,6 flats	.063	1,6		
						.099	2,5		
						.126	3,2		
						.157	4,0		
SJT	12/3	.420	10,8	.875 w/	22,2 w/	.032	0,8	1865	RDD 401
		.450	12,1	.770 flats	19,6 flats	.063	1,6		
						.099	2,5		
						.126	3,2		
						.157	4,0		
S	18/3	.525	13,5	1.109 w/	28,2 w/	.063	1,6	1868	RDD 501
SJT	14/3	.600	15,2	1.000 flats	25,4 flats	.099	2,5		
						.126	3,2		
						.157	4,0		
						.187	4,8		
S	12/3	.600	15,2	1.109 w/	28,2 w/	.063	1,6	1802	RDD 601
SJT	8/3	.700	17,8	1.000 flats	25,4 flats	.099	2,5		
						.126	3,2		
						.157	4,0		
						.187	4,8		

Standard color black. Consult Heyco for white and other colors.

- Automated application equipment speeds assembly to cable and lowers costs while greatly reducing the risk of Carpal Tunnel Syndrome.
- See page 3-1 for Heyco's Automated Pre-Assembly Equipment.
- Installs easily with fingertip pressure into a standard Double "D" hole. No clumsy hand tools required!
- Assembly friendly! Independent of insertion into the panel, RDD Lockit Strain Reliefs self-lock onto the cable. Thus, they may be preassembled offline for final assembly at a later time or remote location, for lower installed cost!
- Multiple panel locking steps secure lockit strain relief into range of panel thicknesses.



Material	6/6 Nylon
Certifications	Recognized under UL File E15331 (far exceeds UL's 35# pull out test)
Flammability Rating	94V-2
Material Temperature Index	257°F (125°C)—Maximum temperature on part not to exceed 221°F (105°C)

Quick Specs