




Heyco® Metric Snap Bushings

- Converts raw-edged holes to smooth ones.
- Locking fingers snap into holes with fingertip pressure.
- Withstands a push back force of 35 pounds.
- Multiple sizes for use in .630" (16,0 mm) to 1.260" (32,0 mm) diameter holes. For other metric sizes, consult Heyco.
- Locks firmly into panel up to .098" (2,5 mm) thick.
- Same design as Heyco Snap Bushings but designed for metric sized mounting holes.

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter				A	B		C		
in.	mm.	in.	mm.	Black	Inside Diameter	Head Diameter	Overall Height	in.	mm.	in.	mm.
.098	2,5	.630	16,0	2142	MSB 16-12	.472	12,0	.728	18,5	.406	10,3
.098	2,5	.787	20,0	2144	MSB 20-16	.630	16,0	.890	22,6	.406	10,3
.098	2,5	.984	25,0	2146	MSB 25-19	.748	19,0	1.094	27,8	.453	11,5
.098	2,5	1.260	32,0	2148	MSB 32-26	1.023	26,0	1.375	34,9	.453	11,5

Standard color black. Consult Heyco for white and other colors.



Quick Specs

Material	6/6 Nylon
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E15331 Certified by the Canadian Standards Association File LR8919
Flammability Rating	94V-2
Material Temperature Index	257°F (125°C)—Maximum temperature on part not to exceed 221°F (105°C)