



Heyco® Rubber Grommets

Mounting Diameter: 0.250" to 0.562"

- Used to protect or cover through holes. Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- 160 sizes available that will accommodate mounting holes ranging from .250" (6,4 mm) to holes as large as 2.50" (63,5 mm) diameter and panel thicknesses from .063" (1,6 mm) to .375" (9,5 mm).
- Rubber grommets are constructed of SBR with an operating temperature range of -40°F (-40°C) to 221°F (105°C).
- SBR grommets have good water resistant characteristics and are suitable for most moderate chemicals and wet or dry organic acids.

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS						
Maximum Thickness		Mounting Hole Diameter				Black	A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.
.063	1,6	.250	6,4	G1004	RG 250-4-2	.125	3,2	.344	8,7	.188	4,8	
.063	1,6	.250	6,4	G1005	RG 250-5-2	.156	4,0	.375	9,5	.188	4,8	
.063	1,6	.250	6,4	G1006	RG 250-5-2A	.156	4,0	.438	11,1	.375	9,5	
.094	2,4	.281	7,1	G1010	RG 281-6-3	.188	4,8	.438	11,1	.219	5,6	
.063	1,6	.312	7,9	G1017	RG 312-6-2	.188	4,8	.406	10,3	.219	5,6	
.063	1,6	.312	7,9	G1018	RG 312-6-2A	.188	4,8	.438	11,1	.188	4,8	
.063	1,6	.312	7,9	G1019	RG 312-6-2B	.188	4,8	.500	12,7	.250	6,4	
.094	2,4	.312	7,9	G1014	RG 312-6-3	.188	4,8	.500	12,7	.281	7,1	
.125	3,2	.312	7,9	G1020	RG 312-6-4	.188	4,8	.438	11,8	.250	6,4	
.188	4,8	.312	7,9	G1022	RG 312-6-6	.188	4,8	.438	11,8	.313	8,0	
.250	6,4	.312	7,9	G1023	RG 312-6-8	.188	4,8	.438	11,8	.375	9,5	
.063	1,6	.312	7,9	G1026	RG 312-7-2	.219	5,6	.438	11,8	.188	4,8	
.094	2,4	.375	9,5	G1033	RG 375-4-3	.125	3,2	.500	12,7	.313	8,0	
.188	4,8	.375	9,5	G1034	RG 375-6-6	.188	4,8	.625	15,9	.375	9,5	
.063	1,6	.375	9,5	G1037	RG 375-8-2	.250	6,4	.563	14,3	.250	6,4	
.094	2,4	.375	9,5	G1038	RG 375-8-3	.250	6,4	.500	12,7	.250	6,4	
.094	2,4	.375	9,5	G1039	RG 375-8-3A	.250	6,4	.563	14,3	.281	7,1	
.063	1,6	.375	9,5	G1042	RG 375-9-2	.281	7,1	.563	14,3	.250	6,4	
.375	9,5	.375	9,5	G1043	RG 375-10-12	.313	8,0	.563	14,3	.500	12,7	
.125	3,2	.406	10,3	G1047	RG 406-9-4	.281	7,1	.625	15,9	.375	9,5	
.063	1,6	.437	11,1	G1052	RG 437-8-2	.250	6,4	.625	15,9	.188	4,8	
.063	1,6	.437	11,1	G1053	RG 437-8-2A	.250	6,4	.625	15,9	.313	8,0	
.125	3,2	.437	11,1	G1056	RG 437-8-4	.250	6,4	.625	15,9	.250	6,4	
.188	4,8	.437	11,1	G1057	RG 437-8-6	.250	6,4	.625	15,9	.313	8,0	
.250	6,4	.437	11,1	G1058	RG 437-8-8	.250	6,4	.625	15,9	.375	9,5	
.063	1,6	.437	11,1	G1061	RG 437-10-2	.313	8,0	.625	15,9	.281	7,1	
.094	2,4	.437	11,1	G1062	RG 437-10-3	.313	8,0	.625	15,9	.313	8,0	
.250	6,4	.500	12,7	G1086	RG 500-10-8	.313	8,0	.625	15,9	.625	15,9	
.063	1,6	.500	12,7	G1089	RG 500-12-2	.375	9,5	.625	15,9	.250	6,4	
.063	1,6	.500	12,7	G1090	RG 500-12-2A	.375	9,5	.688	17,5	.281	7,1	
.125	3,2	.500	12,7	G1092	RG 500-12-4	.375	9,5	.625	15,9	.313	8,0	
.125	3,2	.500	12,7	G1093	RG 500-12-4A	.375	9,5	.625	15,9	.406	10,3	
.156	4,0	.500	12,7	G1094	RG 500-12-5	.375	9,5	.688	17,5	.313	8,0	
.250	6,4	.500	12,7	G1095	RG 500-12-8	.375	9,5	.750	19,1	.500	12,7	
.375	9,5	.500	12,7	G1096	RG 500-12-12	.375	9,5	.625	15,9	.625	15,9	
.188	4,8	.562	14,3	G1110	RG 562-6-6	.188	4,8	.750	19,1	.312	7,9	
.063	1,6	.562	14,3	G1112	RG 562-10-2	.313	8,0	.813	20,7	.313	8,0	
.125	3,2	.562	14,3	G1114	RG 562-10-4	.313	8,0	.813	20,7	.375	9,5	
.188	4,8	.562	14,3	G1115	RG 562-10-6	.313	8,0	.813	20,7	.375	9,5	
.188	4,8	.562	14,3	G1116	RG 562-10-6A	.313	8,0	.813	20,7	.438	11,1	

Standard color black.

