



# Heyco® Rubber Grommets

Mounting Diameter: 1.250" to 2.500"

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter				Black	A Inside Diameter		B Head Diameter		C Overall Height
in.	mm.	in.	mm.		in.		mm.	in.	mm.	in.	mm.
.063	1,6	1.250	31,8	<b>G1311</b>	RG 1250-32-2	1.000	25,4	1.563	39,7	.313	8,0
.188	4,8	1.250	31,8	<b>G1312</b>	RG 1250-32-6	1.000	25,4	1.500	38,1	.438	11,1
.375	9,5	1.250	31,8	<b>G1314</b>	RG 1250-32-12	1.000	25,4	1.500	38,1	.625	15,9
.063	1,6	1.375	34,9	<b>G1320</b>	RG 1375-32-2	1.000	25,4	1.750	44,5	.438	11,1
.125	3,2	1.375	34,9	<b>G1322</b>	RG 1375-32-4	1.000	25,4	1.750	44,5	.500	12,7
.188	4,8	1.375	34,9	<b>G1323</b>	RG 1375-32-6	1.000	25,4	1.750	44,5	.563	14,3
.250	6,4	1.375	34,9	<b>G1324</b>	RG 1375-32-8	1.000	25,4	1.750	44,5	.625	15,9
.375	9,5	1.375	34,9	<b>G1326</b>	RG 1375-32-12	1.000	25,4	1.750	44,5	.750	19,1
.188	4,8	1.375	34,9	<b>G1329</b>	RG 1375-36-6	1.125	28,6	1.875	47,6	.500	12,7
.063	1,6	1.500	38,1	<b>G1347</b>	RG 1500-36-2	1.125	28,6	1.875	47,6	.375	9,5
.156	4,0	1.500	38,1	<b>G1348</b>	RG 1500-38-5	1.188	30,2	1.750	44,5	.406	10,3
.063	1,6	1.500	38,1	<b>G1349</b>	RG 1500-40-2	1.250	31,8	1.875	47,6	.344	8,7
.125	3,2	1.500	38,1	<b>G1350</b>	RG 1500-40-4	1.250	31,8	1.875	47,6	.406	10,3
.188	4,8	1.500	38,1	<b>G1351</b>	RG 1500-40-6	1.250	31,8	2.000	50,8	.625	15,9
.250	6,4	1.500	38,1	<b>G1353</b>	RG 1500-40-8	1.250	31,8	1.750	44,5	.500	12,7
.250	6,4	1.500	38,1	<b>G1354</b>	RG 1500-40-8A	1.250	31,8	2.000	50,8	.516	13,1
.125	3,2	1.625	41,3	<b>G1363</b>	RG 1625-42-4	1.313	33,4	2.000	50,8	.438	11,1
.125	3,2	1.625	41,3	<b>G1364</b>	RG 1625-44-4	1.375	34,9	1.875	47,6	.406	10,3
.063	1,6	1.750	44,5	<b>G1369</b>	RG 1750-48-2	1.500	38,1	2.125	54,0	.438	11,1
.125	3,2	1.750	44,5	<b>G1371</b>	RG 1750-48-4	1.500	38,1	2.125	54,0	.500	12,7
.188	4,8	1.750	44,5	<b>G1372</b>	RG 1750-48-6	1.500	38,1	2.125	54,0	.563	14,3
.250	6,4	1.750	44,5	<b>G1373</b>	RG 1750-48-8	1.500	38,1	2.000	50,8	.500	12,7
.250	6,4	1.750	44,5	<b>G1374</b>	RG 1750-48-8A	1.500	38,1	2.125	54,0	.625	15,9
.375	9,5	1.750	44,5	<b>G1375</b>	RG 1750-48-12	1.500	38,1	2.125	54,0	.750	19,1
.094	2,4	2.000	50,8	<b>G1387</b>	RG 2000-48-3	1.500	38,1	2.375	60,3	.375	9,5
.188	4,8	2.000	50,8	<b>G1390</b>	RG 2000-52-6	1.625	41,3	2.250	57,2	.750	19,1
.125	3,2	2.000	50,8	<b>G1392</b>	RG 2000-56-4	1.750	44,5	2.375	60,3	.375	9,5
.250	6,4	2.000	50,8	<b>G1393</b>	RG 2000-56-8	1.750	44,5	2.500	63,5	.531	13,5
.250	6,4	2.000	50,8	<b>G1394</b>	RG 2000-56-8A	1.750	44,5	2.500	63,5	.560	14,2
.375	9,5	2.000	50,8	<b>G1395</b>	RG 2000-56-12	1.750	44,5	2.500	63,5	.625	15,9
.190	4,8	2.200	55,9	<b>G1404</b>	RG 2.200-64-6	2.000	50,8	2.750	69,9	.560	14,2
.063	1,6	2.375	60,3	<b>G1409</b>	RG 2.375-40-2	1.250	31,8	2.750	69,9	.438	11,1
.190	4,8	2.375	60,3	<b>G1414</b>	RG 2.375-64-6	2.000	50,8	2.750	69,9	.560	14,2
.063	1,6	2.500	63,5	<b>G1418</b>	RG 2.5-40-2	1.250	31,8	2.875	73,0	.438	11,1
.250	6,4	2.500	63,5	<b>G1421</b>	RG 2.5-64-8	2.000	50,8	3.000	76,2	.563	14,3
.063	1,6	2.500	63,5	<b>G1422</b>	RG 2.5-68-2	2.125	54,0	2.875	73,0	.438	11,1
.125	3,2	2.500	63,5	<b>G1423</b>	RG 2.5-68-4	2.125	54,0	2.875	73,0	.438	11,1
.250	6,4	2.500	63,5	<b>G1425</b>	RG 2.5-72-8	2.250	57,2	3.000	76,2	.625	15,9
.328	8,3	2.500	63,5	<b>G1426</b>	RG 2.5-72-10	2.250	57,2	3.000	76,2	.719	18,3
.375	9,5	2.500	63,5	<b>G1427</b>	RG 2.5-72-12	2.250	57,2	3.000	76,2	.750	19,1

Standard color black.

- Used to protect or cover through holes. Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- 160 sizes available that will accommodate mounting holes ranging from .250" (6,4 mm) to holes as large as 2.50" (63,5 mm) diameter and panel thicknesses from .063" (1,6 mm) to .375" (9,5 mm).
- Rubber grommets are constructed of SBR with an operating temperature range of -40°F (-40°C) to 221°F (105°C).
- SBR grommets have good water resistant characteristics and are suitable for most moderate chemicals and wet or dry organic acids.