



Heyco® Polyurethane Adhesive Backed Bumpers

Hemispherical



- Bumpers can be attached to a wide variety of surfaces; aluminum, ceramic, formica, glass, painted surfaces, polyethylene, polypropylene, vinyl, and steel.
- Quick and easy installation—simply peel off backing and press into place. With no holes to drill, and no screws or rivets needed, adhesive backed bumpers will save you time and money.
- Adhesive backed bumpers are nonmarking, nonstaining, skid, and scratch resistant.
- Surface must be clean, dry, and free of grease, oil, and other common solvents to obtain maximum adhesion. Clean surfaces with low strength solvents such as Isopropyl Alcohol or Heptane.
- Recommended storage guidelines: temperature range 40°F (40°C) to 75°F (24°C), humidity range 40% to 60%.
- Clear parts have an anti-yellowing agent.
- Clear bumpers have acrylic-based pressure sensitive adhesive with an end use temperature of 0°F (-18°C) to 250°F (121°C). Black bumpers have a rubber-based pressure sensitive adhesive with an end use temperature of 0°F (-18°C) to 180°F (82°C).

PART NO.		DESCRIPTION	PART SPECIFICATIONS/DIMENSIONS				Pieces per Pad
Clear	Black		A		B		
			Diameter		Height		
		in.	mm.	in.	mm.		
N040	N140	HBA 250-06	.25	6,4	.06	1,6	578
N007	N107	HBA 335-09	.34	8,6	.09	2,3	450
N012	N112	HBA 375-15	.38	9,7	.15	3,8	200
N002	N102	HBA 440-20	.44	11,2	.20	5,1	242
N015	N115	HBA 620-31	.62	15,7	.31	7,9	128
N008	N108	HBA 700-38	.70	17,8	.38	9,7	98
N039	N139	HBA 750-08	.75	19,1	.08	2,0	84

Recognized under the Component Program of Underwriters' Laboratories File E196663.

