




Heyco® Polyurethane Adhesive Backed Bumpers

Cylindrical

PART NO.	DESCRIPTION	PART SPECIFICATIONS/DIMENSIONS					
		A Diameter		B Height		Pieces per Pad	
		in.	mm.	in.	mm.		
N135	CBA 370-19	.37	9,4	.19	4,8	200	
N105	BA 500-06	.50	12,7	.06	1,5	200	
N101	CBA 500-14	.50	12,7	.14	3,6	200	
N106	CBA 500-25	.50	12,7	.25	6,4	200	
N111	CBA 620-40	.62	15,7	.40	10,2	128	
N124	CBA 810-12	.81	20,6	.12	3,0	72	


Recognized under the Component Program of Underwriters' Laboratories File E196663.



Cylindrical Depression

PART NO.	DESCRIPTION	PART SPECIFICATIONS/DIMENSIONS					
		A Diameter		B Height		Pieces per Pad	
		in.	mm.	in.	mm.		
N118	CDBA 500-14	.50	12,7	.14	3,6	200	
N117	CDBA 880-40	.88	22,4	.40	10,2	72	
N130	CDBA 1810-60	1.81	46,0	.60	15,2	1	

Recognized under the Component Program of Underwriters' Laboratories File E196663.



- Bumpers can be attached to a wide variety of surfaces: aluminum, ceramic, formica, glass, painted surfaces, polyethylene, polypropylene, vinyl, and steel.
- Quick and easy installation—simply peel off backing and press into place. With no holes to drill, and no screws or rivets needed, adhesive backed bumpers will save you time and money.



- Adhesive backed bumpers are nonmarking, nonstaining, skid, and scratch resistant.
- Surface must be clean, dry, and free of grease, oil, and other common solvents to obtain maximum adhesion. Clean surfaces with low strength solvents such as Isopropyl Alcohol or Heptane.
- Recommended storage guidelines: temperature range 40°F (40°C) to 75°F (24°C), humidity range 40% to 60%.
- Bumpers have a rubber-based pressure sensitive adhesive with an end use temperature of 0°F (-18°C) to 180°F (82°C).