



Heyco® Feet of Strength™

FSR—Feet with Push Rivet



PANEL DIMENSIONS						PART NO.	DESCRIPTION	PART DIMENSIONS						
Mounting Hole Size		Thickness Range						Black	A Overall Height		B Top Diameter		C Bottom Diameter	
		Minimum	Maximum	in.	mm.				in.	mm.	in.	mm.		
.122	3,1	.031	0,8	.071	1,8	2517	FSR 1221-031	.217	5,5	.531	13,5	.559	14,2	
.142	3,6	.039	1,0	.079	2,0	2520	FSR 1415-039	.157	4,0	.394	10,0	.425	10,8	
.142	3,6	.079	2,0	.118	3,0	2521	FSR 1415-079	.157	4,0	.394	10,0	.425	10,8	
.161	4,1	.031	0,8	.071	1,8	2522	FSR 1616-031	.165	4,2	.787	20,0	.827	21,0	
.161	4,1	.071	1,8	.110	2,8	2523	FSR 1616-071	.165	4,2	.787	20,0	.827	21,0	
.161	4,1	.075	1,9	.110	2,8	2527	FSR 1623-071	.236	6,0	.787	20,0	.827	21,0	
.161	4,1	.114	2,9	.157	4,0	2528	FSR 1623-110	.236	6,0	.787	20,0	.827	21,0	
.161	4,1	.083	2,1	.118	3,0	2530	FSR 1631-079	.315	8,0	.787	20,0	.827	21,0	
.161	4,1	.039	1,0	.079	2,0	2532	FSR 1635-039	.354	9,0	.551	14,0	.591	15,0	
.161	4,1	.079	2,0	.118	3,0	2533	FSR 1635-079	.354	9,0	.551	14,0	.591	15,0	

Standard color black.

- Requires only fingertip pressure for fast, easy installation.
- May be released from inside the panel.
- Multiple sizes range in height from .217" (5,5 mm) to .354" (9,0 mm).
- Molded from ethylene vinyl acetate.

