



# Heyclip™ Push Mount Wire Clips

For Panels .020" to .080" Thick

- Push mount design allows for fast installation.
- Made of 6/6 Nylon with a 94V-2 flammability rating.
- Releasable and reusable wire clip.
- Bayonet design allows from .020" panel thickness to .150" (3,81 mm). Bayonet snap locks into a .250" (6.35 mm) hole and will hold a 25 pound continuous load or a 50 pound impact load.
- Multiple sizes available for bundles from .187" (4,7 mm) to 1.00" (25,4 mm).

MAX. BUNDLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS													
in.	mm.			A		B		C		D		E		F			
.187	4,7	<b>3845</b>	PMWC 187-20	.55	14,0	1.00	25,4	.39	9,9	.38	9,7						
.250	6,4	<b>3846</b>	PMWC 250-20	.58	14,7	1.00	25,4	.44	11,2	.41	10,4						
.375	9,5	<b>3847</b>	PMWC 375-20	.65	16,5	1.00	25,4	.53	13,5	.50	12,7						
.500	12,7	<b>3848</b>	PMWC 500-20	.77	19,6	1.19	30,2	.72	18,3	.60	15,2	.20	5,1	.30	7,6		
.750	19,1	<b>3849</b>	PMWC 750-20	.88	22,4	1.38	35,1	.97	24,6	.67	17,0						
1.000	25,4	<b>3853</b>	PMWC 1000-20	1.37	34,8	1.88	47,8	1.30	33,0	1.00	25,4						

Standard color gray.




## For Panels 0.090" to .150" Thick


MAX. BUNDLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS													
in.	mm.			A		B		C		D		E		F			
.187	4,7	<b>3880</b>	PMWC 187-90	.55	14,0	1.00	25,4	.39	9,9	.38	9,7						
.250	6,4	<b>3881</b>	PMWC 250-90	.58	14,7	1.00	25,4	.44	11,2	.41	10,4						
.375	9,5	<b>3882</b>	PMWC 375-90	.65	16,5	1.00	25,4	.53	13,5	.50	12,7						
.500	12,7	<b>3883</b>	PMWC 500-90	.77	19,6	1.19	30,2	.72	18,3	.60	15,2	.20	5,1	.37	9,4		
.750	19,1	<b>3884</b>	PMWC 750-90	.88	22,4	1.38	35,1	.97	24,6	.67	17,0						
1.000	25,4	<b>3885</b>	PMWC 1000-90	1.37	34,8	1.88	47,8	1.30	33,0	1.00	25,4						

Standard color gray.


### Push Mount Wire Clips Instructions





Simply insert base of clip into .250" hole.



Heyclip opens easily for access to bundle.




Unique lock/release feature operates easily and locks securely. When closed, Heyclip will not open until tab is released.



Release tab provides easy opening without forcing.

Barbed locking element insures reliable retention.



Quick lock/release allows fast lock-up and easy access to wire bundle.

Unique design of push mount permits fast installation and provides high pull-out resistance.