



# Heyco® Cable Wrap

## Standard Cut–Polyethylene (94V-0)

- Bundles and protects cables, wires, tubing, and hoses from .125" (3,2 mm) to 2.00" (50,8 mm) diameters.
- Absorbs vibration, insulates cables, and resists abrasion.
- Easy to use: Just twist on wire!
- Allows breakouts of single/multiple wires and re-routing of replacement wires.
- Multiple sizes available.
- Polyethylene and nylon material products are available in UV black or natural color.

- Conforms to the following Mil, Federal, and ASTM specifications:

–Polyethylene Cable Wrap–  
UV Black and Natural

Fed. Spec LP390  
Mil I-631D  
Mil P-21922B

–Nylon Cable Wrap–UV Black

ASTM D4066 Group 2  
Fed. Spec LP-410A  
Mil T-47287A Type II  
AS 1294

–Nylon Cable Wrap–Natural

ASTM D4066 Group 2  
Fed. Spec LP-410A

–Standard Cut–Polyethylene  
94V-0, 169°F (76°C)–214°F (101°C)

–Standard Cut–Nylon  
94V-2, 185°F (85°C)–200°F (93°C)

BUNDLE RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS					
Minimum Diameter		Maximum Diameter		UV Black	Natural		A Outside Diameter		B Pitch		C Thickness	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.
.125	3,2	.375	9,5	<b>8904</b>	<b>8905</b>	CW 187 PE	.187	4,8	.250	6,3	.031	0,8
.187	4,8	.500	12,7	<b>8908</b>	<b>8909</b>	CW 250 PE	.250	6,3	.375	9,5	.045	1,1
.312	7,9	.750	19,1	<b>8912</b>	<b>8913</b>	CW 375 PE	.375	9,5	.438	11,1	.052	1,3
.375	9,5	1.000	25,4	<b>8916</b>	<b>8917</b>	CW 500 PE	.500	12,7	.500	12,7	.062	1,6
.500	12,7	1.250	31,8	<b>8920</b>	<b>8921</b>	CW 625 PE	.625	15,9	.625	15,9	.062	1,6
.750	19,1	1.500	38,1	<b>8924</b>	<b>8925</b>	CW 750 PE	.750	19,1	.750	19,1	.065	1,7
1.000	25,4	2.000	50,8	<b>8928</b>	<b>8929</b>	CW 1000 PE	1.000	25,4	1.000	25,4	.080	2,0

Standard colors UV black or natural.  
Temperature not to exceed 50°C.

## Standard Cut–Nylon (94V-2)

BUNDLE RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS					
Minimum Diameter		Maximum Diameter		UV Black	Natural		A Outside Diameter		B Pitch		C Thickness	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.
.125	3,2	.375	9,5	<b>8936</b>	<b>8937</b>	CW 187 N	.187	4,8	.250	6,3	.020	0,5
.187	4,8	.500	12,7	<b>8940</b>	<b>8941</b>	CW 250 N	.250	6,3	.375	9,5	.025	0,6
.312	7,9	.750	19,1	<b>8944</b>	<b>8945</b>	CW 375 N	.375	9,5	.438	11,1	.035	0,9
.375	9,5	1.000	25,4	<b>8948</b>	<b>8949</b>	CW 500 N	.500	12,7	.500	12,7	.035	0,9
.500	12,7	1.250	31,8	<b>8952</b>	<b>8953</b>	CW 625 N	.625	15,9	.625	15,9	.032	0,8
.750	19,1	1.500	38,1	<b>8956</b>	<b>8957</b>	CW 750 N	.750	19,0	.750	19,1	.032	0,8
1.000	25,4	2.000	50,8	<b>8960</b>	<b>8961</b>	CW 1000 N	1.000	25,4	1.000	25,4	.032	0,8

Standard colors UV black or natural.  
Temperature not to exceed 50°C.

