



Heyco® Turn-2-Lock Cordset Components

15 Amp



- Snap together nylon premold female housing eliminates the need for expensive cammed molds.
- Easy loading for increased molding efficiency.
- Uses inexpensive Heyco load pins (consult Heyco for details on our complete line of blades and pins).
- Reduces PVC usage and allows more cavities per mold.

PART NO.	DESCRIPTION	WIRE RANGE	FEEDS	DIE	TOOL PACK	CRIMP PUNCH	AVIL
Male							
**6110	TL-L5-15W&B Brass	16-10 AWG	Bulk	6110UXX5	B958B/B959B	C663	C667
6111	TL-L5-15W&B Tin	16-10 AWG	Bulk	6111UXX5	B958B/B959B	C663	C667
6126	TL-L5-15W&B Nickel	16-10 AWG	Bulk	6126UXX5	B958B/B959B	C663	C667
6112	TL-L5-15-G Brass	16-10 AWG	Bulk	6112UXX5	B958B/B959B	C663	C667
6113	TL-L5-15-G Tin	16-10 AWG	Bulk	6113UXX5	B958B/B959B	C663	C667
6127	TL-L5-15-G Nickel	16-10 AWG	Bulk	6127UXX5	B958B/B959B	C663	C667
6130	TL-L7-15-G Brass	16-10 AWG	Bulk	6130UXX5	B958B/B959B	C663	C667
6134	TL-L6-15-G Brass	16-10 AWG	Bulk	6134UXX5	B958B/B959B	C663	C667
6150	T2L-15-A	18-14 AWG	Bulk	6134UXX5	B958B/B959B	C663	C667
6152	T2L-L5-15-GND	18-14 AWG	Bulk	6134UXX5	B958B/B959B	C663	C667
6160	T2L-15A-GRD	18-14 AWG	Bulk	6134UXX5	B958B/B959B	C663	C667
6164	T2L-15A-GRD	18-14 AWG	Bulk	6134UXX5	B958B/B959B	C663	C667

**Can be used for L6 and L7-15 configurations.

Female							
7550	TLR-L5-15	16-10 AWG	left to right	7550UXX5	B972L/B973L	C784	C783
7756	2 PC L5-15 Premold	N/A	—	—	—	—	—
7551	TLR-L7-15	16-10 AWG	left to right	7551UXX5	B972L/B973L	C784	C783
7752	2-pc L7-15 Premold	N/A	—	—	—	—	—

