





## Heyco® Aluminum Solderless Connectors

WIRE RANGE (AWG)	PART NO.	DESCRIPTION	HEIGHT WITH MAX. WIRE		A Width		B Length		Bolt Size	
			in.	mm.	in.	mm.	in.	mm.	in.	mm.
			6-14	1863	A35	1/2	12,7	3/8	9,5	1-1/16
2-14	1864	A90	9/16	14,3	1/2	12,7	1-5/32	29,4		

- Compact design—lightweight yet strong.
- Requires no special installation tools.
- Electro-tin plated for low contact resistance and corrosion protection when used with copper conductors.
- Ports are marked with catalog description and conductor range.
- UL and CSA certified for use with copper and aluminum conductors.







## Heyco® Copper Lug Connectors Copper Single Hole Offset Lugs



WIRE RANGE (AWG)	PART NO.	DESCRIPTION	CURRENT RATING AMPS	HEIGHT WITH MAX. WIRE		A Tang Width		B Length		Bolt Size	
				in.	mm.	in.	mm.	in.	mm.	in.	mm.
				10-14	1850	CB 25	25	11/16	17,5	5/16	7,9
6-14 & Comb**	1851	CB 35	50	3/4	19,1	3/8	9,5	1-3/16	30,2	3/16	4,8

\*\*10/2, 12/2, 14/2, 10/1 and 12/1, 12/1 and 14/1.

- 100% conductivity for highest efficiency.
- Completely reusable.
- Requires no special installation tools.
- UL listed and CSA certified for use with copper conductors.
- Marked with catalog description and conductor range.



Material  
Certifications

- 6061-T6 aluminum alloy; electrolytic copper
- UL Listed Underwriters' Laboratories File E80121
- CSA Certified by the Canadian Standards Association File LR211103 94V-0

Flamability Rating

Quick Specs