

“Stay Connected” with



Liquid Tight Cordgrips

a PennEngineering® Company



HEYbrid™ Plated Steel Liquid Tight Cordgrips




Straight-Thru, NPT Hubs

Don't get SKU'ed: More Cable Range, Fewer SKU's –
Genetically engineered to destroy your inventory monster!
The Ultimate in Liquid Tight Strain Relief Protection

- **HEYCo-molded gripping finger/gland technology** accommodates the **widest cable range** over the **fewest sku's**.
- Rolled grease-free threads **prevent galling** and allow for multiple assemblies and disassemblies. No messy, unsightly thread lubrication required.
- Approved for **NEMA 4, 4X, 6 and 6P** applications.
- Self-retaining sealing rings eliminate the need for an O-Ring groove, thus **reducing cost**.
- Sealing washer required for through hole applications only.
- Typical applications: Control cabinets, car washes, hot tubs, instrumentation, carpet cleaning machines, underground for direct burial or submersed up to 130 ft. (70 PSIG).
- Constructed from corrosion resistant Zinc Plated steel.
- Resistant to salt water, acids and most chemicals.
- Patent pending.
- DFARS Compliant

CABLE DIA. RANGE				PART NO.	DESCRIPTION	UL or RA	PART DIMENSIONS									
Minimum		Maximum					A Clearance Hole Dia.	B Max. O.A. Length		C Thread Length		D Wrenching Nut Thickness		E Wrenching Nut Flat Size		
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.	in.	mm.		
HEYCo-molded Finger/Gland																
.065	1,7	.210	5,3	M6200	RPSCG 1/4	cULus	.540	13,7	1.29	32,8	.40	13,2	.20	5,1	.75	19,1
.115	2,9	.250	6,4	M6201	PSCG 1/4	cULus										
.065	1,7	.230	5,8	M6202	RPSCG 3/8	cULus	.680	17,3	1.39	35,3	.41	10,4	.20	5,1	.88	22,4
.105	2,7	.315	8,0	M6203	PSCG 3/8	cULus										
.095	2,4	.290	7,4	M6206	RPSCG 1/2	cULus	.875	22,2	1.69	42,9	.53	13,5	.20	5,1	1.06	26,9
.170	4,3	.450	11,4	M6207	PSCG 1/2	cULus										
.180	4,6	.400	10,1	M6208	RPSCG LL 1/2	cULus	.875	22,2	1.81	46,0	.53	13,5	.20	5,1	1.25	31,8
.260	6,6	.545	13,8	M6209	PSCG LL 1/2	cULus										
.250	6,4	.490	12,4	M6210	RPSCG 3/4	cULus	1.109	28,2	1.93	49,0	.55	14,0	.20	5,1	1.31	33,3
.435	11,0	.705	17,9	M6211	PSCG 3/4	cULus										
.490	12,4	.785	19,9	M6212	RPSCG 1	cULus	1.375	34,9	2.29	58,1	.69	17,5	.20	5,1	1.75	44,5
.590	15,0	1.000	25,4	M6213	PSCG 1	cULus										
Discrete Finger & Gland																
.787	20,0	1.020	26,0	M6215	RPSCG 1-1/4	cULus	1.734	44,0	2.56	65,0	.71	18,0	.25	6,4	2.25	57,2
.865	22,0	1.260	32,0	M6216	PSCG 1-1/4	cULus										
1.000	25,4	1.240	31,5	M6217	RPSCG 1-1/2	cULus	1.984	50,4	2.69	67,1	.73	18,5	.25	6,4	2.50	63,5
1.230	31,2	1.560	39,6	M6218	PSCG 1-1/2	cULus										
1.160	29,5	1.350	34,3	M6219	RPSCG 2	cULus	2.469	62,7	2.92	74,2	.76	19,3	.25	6,4	2.75	69,9
1.450	36,8	1.730	44,0	M6220	PSCG 2	cULus										

The HEYCo-molded Finger, Gland & Seat



Quick Specs

Material	Zinc Plated Steel Body and sealing nut with nylon 6/6 and TPE co-molded finger/gland assembly SBR Sealing Washer
Certifications	cULus Listed under Underwriters' Laboratories File E51579 cRAus Recognized under Underwriters' Laboratories File E51579
Flammability Rating	94V-2
Temperature Range	-40°F (-40°C) to 221°F (105°C)
IP Rating	IP68 (70 PSI, 5 BAR)