

“Stay Connected” with



HEYware Products


a PennEngineering® Company



HEYClip™ Barbed Push Fasteners

WILL FIT THESE PANELS						PART NO.	DESCRIPTION	PART DIMENSIONS							
MOUNTING HOLE DIA.		ASSEMBLED PANEL THICKNESS						Black	A Length		B Head Height		C Head Diameter		
		Min.	Max.	in.	mm.				in.	mm.	in.	mm.	in.	mm.	
.157	4,0	.08	2,1	.17	4,3	11530	HBPF 157-339-315 BLACK	.34	8,6	.04	1,0	.31	8,0		
		.08	2,1	.28	7,2	11531	HBPF 157-437-315 BLACK	.44	11,1						
		.22	5,7	.42	10,7	11532	HBPF 157-591-315 BLACK	.59	15,0						
		.08	2,1	.17	4,3	11533	HBPF 157-339-472 BLACK	.34	8,6	.06	1,5	.47	12,0		
				.28	7,2	11534	HBPF 157-437-472 BLACK	.44	11,1						
				.42	10,7	11535	HBPF 157-591-472 BLACK	.59	15,0						
.187	4,8	.08	2,1	.17	4,3	11536	HBPF 187-339-315 BLACK	.34	8,6	.04	1,0	.31	8,0		
		.08	2,1	.28	7,2	11537	HBPF 187-437-315 BLACK	.44	11,1						
		.22	5,7	.42	10,7	11538	HBPF 187-591-315 BLACK	.59	15,0						
.250	6,4	.08	2,1	.17	4,3	11539	HBPF 250-339-472 BLACK	.34	8,6	.06	1,5	.47	12,0		
		.08	2,1	.28	7,2	11540	HBPF 250-437-472 BLACK	.44	11,1						
		.22	5,7	.42	10,7	11541	HBPF 250-591-472 BLACK	.59	15,0						
.281	7,1	.15	3,8	.42	10,7	11542	HBPF 281-591-315 BLACK	.59	15,0	.04	1,0	.31	8,0		
		.27	6,9	.56	14,2	11543	HBPF 281-748-315 BLACK	.75	19,0						
		.15	3,8	.42	10,7	11544	HBPF 281-591-472 BLACK	.59	15,0						
		.27	6,9	.56	14,2	11545	HBPF 281-748-472 BLACK	.75	19,0	.06	1,5	.47	12,0		
				.15	3,8	.42	10,7	11546	HBPF 281-591-630 BLACK					.59	15,0
				.27	6,9	.56	14,2	11547	HBPF 281-748-630 BLACK					.75	19,0


- Saves time by installing with finger-tip pressure – no tools required!
- Low insertion force but high extraction force



HEYClip™ Fastener Plug

WILL FIT THESE PANELS				PART NO.	DESCRIPTION	PART DIMENSIONS						
MOUNTING HOLE DIA.		MAX. ASSEMBLED PANEL THICKNESS				Black	A Length		B Head Height		C Head Diameter	
		in.	mm.				in.	mm.	in.	mm.	in.	mm.
.150	3,8	.311	7,9	9001	FP 150-311	.45	11,5	.07	1,8	.31	8,0	

Standard color black. For other colors consult Heyco.



	HBPF	FP
Material	Nylon 6/6	Acetal (POM)
Flammability Rating	94V-2	94-HB
Temperature Range	40°F (-40°C) to 185°F (85°C)	-4°F (-18°C) to 220°F (104°C)