



## HEYClip™ Wave Locks


### Wave Locks - Standard

BUNDLE DIAMETER RANGE		PART NO. Natural	DESCRIPTION	OVERALL HEIGHT C	
in.	mm.			in.	mm.
<b>WL Series</b>					
.13 - .15	3,2 - 3,8	<b>12085</b>	WL 125	.48	12,2
.16 - .24	4,1 - 6,1	<b>12086</b>	WL 200	.82	20,7
.20 - .30	5,1 - 7,6	<b>12087</b>	WL 250	.91	23,0
.30 - .40	7,6 - 10,2	<b>12088</b>	WL 350	1.03	26,2
.70 - .80	17,8 - 20,3	<b>12091</b>	WL 750	1.52	38,6

**NEW!**

- Part Description Key: WL XXX, where XXX = Average Bundle Diameter (inches).
- Barreled ends for greater holding power.
- Smooth rounded edges won't cut into cable's insulations - or installer's hand.
- Locking ends twist into place with fingertip pressure.

Standard color natural.



Wave Locks-Standard




### Wave Locks - Side Entry - Arrowhead Mount

BUNDLE DIAMETER RANGE		PART NO. Natural	DESCRIPTION	OVERALL HEIGHT C	
in.	mm.			in.	mm.
<b>WL-90 Series</b> For .063" (1,6 mm) thick panels					
.50 - .60	12,7 - 15,2	<b>12094</b>	WLS 550-90	.90	22,8

Standard color natural. Natural 94V-0 material available, consult Heyco.

- Part Description Key: WLS XXX-90, where XXX = Average Bundle Diameter (inches).
- .187" (4,8 mm) diameter mounting hole.



Wave Locks-Arrowhead

Material	Nylon 6/6
Flammability Rating	94V-2
Temperature Range	32°F (0°C) 185°F (85°C)

Quick  
Specs