

“Stay Connected” with



Solar Power Components

a PennEngineering® Company






**ALL NEW  
PRODUCT!**

## Heyco® Helios® Clip – Blind Mount

PANEL THICKNESS RANGE				WIRE DIAMETER RANGE 1-2 Wires	PART NO.	DESCRIPTION	MOUNTING HOLE DIA. A		OVERALL HEIGHT C	
Minimum		Maximum					in.	mm.	in.	mm.
<b>1-2 Wires</b>										
.028	0,7	.250	6,4	.230 (5,8 mm) - .315 (8,0 mm) each cable	<b>S6520</b> <b>S6560</b>	Helios Clip 100 Pack Helios Clip Bulk	.260	6,6	.96	24,4

- The jersey pine tree mounting style installs easily with superior holding power.
- UV rated nylon protects from corrosion due to outdoor exposure.
- Installs into .260" (6,6 mm) mounting hole.
- Holds up to 2 cables between .230 - .315" (5,8 - 8,0 mm) each.
- Cables install with fingertip pressure.
- Molded from our robust UV rated nylon 6/6 for our Solar 20 Year Warranty.



MOUNTING HOLE

Material Heat Stabilized, UV Rated Nylon 6/6 Black  
 Flammability Rating 94V-2  
 Temperature Range Dynamic -4°F (-20°C) to 185°F (85°C)

*Quick  
Specs*