

“Stay Connected” with



Strain Relief Bushings

a PennEngineering® Company





ALL NEW PRODUCTS!

Heyco® Brass Clamping Strain Reliefs

- Extra pull-out resistance
- For Heyco Liquid Tight Clamping Cordgrips, see page 3-45.
- Locknuts not included. For metal locknut specifications or to order locknuts separately, see page 3-48.

CABLE DIAMETER RANGE				PART NO.	THREAD SIZE	PART DIMENSIONS							
Minimum		Maximum				A Clearance Hole Dia.		B Max. O.A. Length		C Thread Length		D Wrenching Flat Size	
in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	in.	mm.
PG Hubs													
.157	4,0	.315	8,0	14875	PG7	.492	12,5	.59	15,0	.24	6,0	.67	17
.236	6,0	.394	10,0	14876	PG9	.598	15,2	.67	17,0	.24	6,0	.79	20
.236	6,0	.472	12,0	14877	PG11	.732	18,6	.67	17,0	.24	6,0	.87	22
.276	7,0	.591	15,0	14878	PG13	.827	21,0	.71	18,0	.28	7,0	.94	24
.354	9,0	.669	17,0	14879	PG16	.886	22,5	.75	19,0	.28	7,0	1.06	27
.472	12,0	.866	22,0	14880	PG21	1.114	28,3	.87	22,0	.31	8,0	1.38	35
.709	18,0	1.181	30,0	14881	PG29	1.469	37,3	.91	23,0	.31	8,0	1.65	42
.945	24,0	1.417	36,0	14882	PG36	1.874	47,6	1.10	28,0	.39	10,0	2.17	55
Metric Hubs													
.197	5,0	.315	8,0	14884	M12 x 1,5	.472	12,0	.79	20,0	.39	10,0	.63	16
.236	6,0	.413	10,5	14885	M16 x 1,5	.630	16,0	.83	21,0	.39	10,0	.75	19
.315	8,0	.591	15,0	14886	M20 x 1,5	.787	20,0	.87	22,0	.39	10,0	.94	24
.492	12,5	.807	20,5	14887	M25 x 1,5	.984	25,0	.94	24,0	.43	11,0	1.18	30
.669	17,0	1.004	25,5	14888	M32 x 1,5	1.260	32,0	1.10	28,0	.51	13,0	1.42	36
.945	24,0	1.299	33,0	14889	M40 x 1,5	1.575	40,0	1.18	30,0	.51	13,0	1.81	46



Quick Specs

Material: Nickel-Plated Brass body with Stainless Steel screws
 Temperature Rating: -58°F (-50°C) to 572°F (300°C)
 IP Rating: IP 20