

"Stay Connected" with



HEYware Products


a PennEngineering® Company

## Heyco-Flex™ V Nylon Slit Tubing

IMPROVED

NOMINAL DIAMETER	PART NO. Black	DESCRIPTION	PART DIMENSIONS						INSTALLATION TOOL PART NO.
			A Outside Diameter		B Inside Diameter		Wall Thickness Range		
in.			in.	mm.	in.	mm.	in.	mm.	
1/4	1635B	HF5B 1/4	.40-.38	10,2-9,5	.27-.24	6,8-6,0	0.004	0,11	8889
3/8	1637B	HF5B 3/8	.53-.50	13,4-12,6	.38-.34	9,7-8,7	0.005	0,12	
7/16	1638B	HF5B 7/16	.60-.57	15,2-14,6	.44-.40	11,1-10,1			
1/2	1639B	HF5B 1/2	.70-.66	17,8-16,9	.52-.47	13,1-12,0			
5/8	1641B	HF5B 5/8	.84-.81	21,3-20,5	.64-.60	16,2-15,3	0.006	0,15	8890
3/4	1642B	HF5B 3/4	.94-.91	23,9-23,1	.78-.75	19,9-19,0			8891
1	1643B	HF5B 1	1.29-1.25	32,9-31,7	1.04-.99	26,5-25,2			8892
1-1/4	1646B	HF5B 1-1/4	1.50-1.45	38,1-36,7	1.26-1.20	31,9-30,5			
1-1/2	1649B	HF5B 1-1/2	1.95-1.87	49,5-47,4	1.65-1.57	41,8-39,8			

Standard color black.



Heyco-Flex™ V Slit Tubing




- Slit design allows side entry and encirclement of preassembled harnesses and capillary tubes.
- Unique slit design allows for wire breakouts.
- Heyco-Flex V is lightweight and flexible, yet durable enough to meet your wire management requirements.
- Multiple sizes 1/4" to 1-1/2".
- All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.
- Quick installation; cuts with utility knife, PVC cutter or Heyco cutting tool #8340.


## Heyco® Nylon Corrugated Conduit/Slit Tubing – HPASS Series

Highly Flexible Polyamide Nylon 6

NOMINAL SIZE	PART NO. Black		DESCRIPTION	PART DIMENSIONS						Roll Length			
	94V-2	94V-0		Wall Thickness	Inside Bend Radius		A Inside Diameter		B Outside Diameter		Ft.	M.	
				in.	mm.	in.	mm.	in.	mm.	in.	mm.		
10 mm	F8450	F8481	HPASS 10 mm 50M SLIT COIL	.012	0,3	0.59	15,0	0.24	6,2	0.39	10,0	164	50
13 mm	F8452	F8482	HPASS 13 mm 50M SLIT COIL			0.79	20,0	0.38	9,6	0.51	13,0		
16 mm	F8454	F8484	HPASS 16 mm 50M SLIT COIL			1.18	30,0	0.47	12,0	0.62	15,8		
21 mm	F8456	F8486	HPASS 21 mm 50M SLIT COIL	.02	0,5	1.57	40,0	0.65	16,5	0.84	21,2	82	25
28 mm	F8460	F8492	HPASS 28 mm 50M SLIT COIL			2.17	55,0	0.88	22,3	1.12	28,5		
34 mm	F8464	F8494	HPASS 34 mm 50M SLIT COIL			2.56	65,0	1.11	28,2	1.36	34,5		
42 mm	F8466	F8496	HPASS 42 mm 25M SLIT COIL	.028	0,7	3.15	80,0	1.42	36,0	1.67	42,5	82	25
54 mm	F8468	F8498	HPASS 54 mm 25M SLIT COIL			3.74	95,0	1.85	47,1	2.15	54,5		



	HF5B	HPASS
Material	Nylon 6	Nylon 6 (PA6)
Flammability Rating	94HB (not UL rated)	94V-2 and 94V-0 Halogen Free
Temperature Range	-40°F (-40°C) to 257°F (125°C) Continuous -40°F (-40°C) to 300°F (149°C) Intermittent	-4°F (-20°C) to 221°F (105°C)



### Type HPASS

- UV resistant.
- Low fire hazard.
- Low smoke and toxicity.
- Halogen, sulphur, and phosphorus free.
- Highly flexible and high fatigue life.
- Lightweight and low installed cost.
- For use with all types of equipment, machinery, pumps, motors, and HVAC equipment.
- 10 mm thru 54 mm nominal sizes.
- Highly resistant to abrasion, oil, and solvents.
- Suitable for use in outdoor locations.
- Maximum flexibility, can be used in extremely tight quarters. Bend radius of HPASS Series is equal to its outside diameter.