

“Stay Connected” with



Solar Power Components


a PennEngineering® Company



Heyco® Liquid Tight PV Connector Cap

- All-in-one solution to protecting the exposed end of any unsecured 4 mm PV connector.
- Simple push-in with quarter-turn feature keeps connector cap in place.
- Plugs in to male or female end of unsecured 4 mm PV connector.
- Protects unused and exposed 4 mm PV connectors from liquids, insects and dust particulate until ready for final installation.
- Meets a minimum of IPX4 on all 4 mm PV connectors on the market.
- Meets IP68 for the most popular 4 mm PV connector on the market, the Staubli MC4.

PART NO.	DESCRIPTION	PART DIMENSIONS					
		A		B		C	
		in.	mm.	in.	mm.	in.	mm.
S6254	LTPVCC YELLOW 100/BAG	0.85	21,6	0.80	20,3	1.43	36,3
S6255	LTPVCC YELLOW BULK						
S6256	LTPVCC WHITE 100/BAG						
S6257	LTPVCC WHITE BULK						



*Quick
Specs*

Material
Temperature Range

Heat Stable, UV Rated Nylon 6/6 – Color: Yellow/White
-40°F (-40°C) to 221°F (105°C)

1-LTPVCC

1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com